

Star Ring EV AC Charger

7kW modern home charge hub



SPARKLEARTH



CHINESE-EV.COM

Technical Specifications

Electrical Parameters	
Output power	7.4kW
Efficiency	≥ 96% (Half load above)
AC output type	Type 2
Metering method	MID meter
Output voltage	AC230V
Output current	0~32A
Input voltage	AC230V
Measurement accuracy	Class 1.0
Frequency	50Hz
Efficiency	≥ 96%
Power coefficient	≥ 0.99APFC (Half load above)
Leakage protection	A+6 (30mA AC+6ma DC)
Structure and Physical Parameters	
Length	195mm
Width	88mm
Hight	350mm
Enclosure materials	ABS+PC
Enclosure rating	IP65
Color	Black
Operating temperature	-20℃~55℃
Altitude	≤ 2000m
Relative humidity	5%~95%

Noise level	< 65dB
Number of guns	Single cable/socket
Interface and Connectivity	
Authorization	RFID/QR Code
Communication protocol	OCCPI.6J
Charging method	Set out
Interface	Card Reader
Network connection	Ethernet/4G
Safety and Standard	
Safety Protection	Overload, input under/over voltage, output overcurrent/short-circuit, leakage, over-temperature, lightning, antirust, anti-inverse, scram Protection
Tri-proof	Moisture-proof, mildew-proof, salt spray-proof
Installation	Stand/wall



Chengdu THD Co., Ltd

Address: No.1725, Floor 17, Unit 1. Building 2, No. 18, 1st South
Dongsi Road, Chengdu High-Tech Zone, China

Web: www.chinese-ev.com

Tel: +8618030500428

WhatsApp: +8619950114828

Email: info@chinese-ev.com

©2023 Chengdu THD Co., Ltd
All Rights Reserved